

# Streamline

## Formerly known as Snap-Loc

Elevate your roof with StreamLine™ 12IN – the next-generation standing seam metal roof panel, formerly known as Snap-Loc, now reengineered and significantly enhanced for superior performance, easier installation, and stunning aesthetics. Some key upgrades are:

Pre-slotted fastener flange

Factory notching and tabbing

Fully reversible design

New striations option

with a patented no-siphon dry lock seam, with a unique reversing feature to allow installation of panels from both directions – starting at any location. The panel is designed with softer, less industrial lines to provide a more architecturally pleasing appearance.

[Code Compliance UL Evaluation Report UL ER25913-01](#)

## Features & Benefits

### **Manufactured in Sacramento, CA**

12" Coverage Option

26 gauge Tru-Gauge™ ArmorTech™ Painted Steel

Factory-notched and tabbed panels available

Vertical interlocking application: allows installation from both directions starting at any location

Patented no-siphon lock seam

1" vertical rib with  $\frac{3}{8}$ " flat top for ease of flashing attachment

Concealed fasteners: fasteners cannot leak

Pre-slotted fastener flange: allows expansion/contraction of panel (high wind clips available for panel length over 35')

3:12 minimum pitch recommended (for lower pitches please inquire)

Standard panel lengths 4' to 35' – not notched

Standard panel lengths 1' to 35' – notched and tabbed (for longer lengths, please inquire)

Panel options: Striations and Accent Ribs



## Material Specifications

26 gauge ArmorTech™ SMP Painted Steel G-90 Galvanized or ZINCALUME® AZ-50

26 gauge bare ZINCALUME® Plus AZ-55 (No finish warranty – 25 year perforation warranty)

## Testing

UL Construction No. 529

UL 580 Class 90 – Wind Uplift

UL 790 Class A (ASTM E108) – Fire rated

UL 2218 Class 4 Impact (hail) rated (StreamLine™ carries its UL Classifications under the Easy-Lock™ profile designation)

ASTM A653/A924 – G90 Galvanized

ASTM A792 – ZINCALUME/Galvalume AZ-50/55

ASTM E2886 – Ember Resistant ridge/endwall/peak flashings available

## Finishes

14 Standard Colors, ZINCALUME® Plus

ArmorTech™ Paint System – excellent in exterior durability and color retention

Color pigments are specially designed to reflect infrared light, reducing heat gain to dwelling, and conform with ENERGY STAR® criteria

Superior quality, two coat SMP resin system at 1 mil. thickness

40-year residential paint warranty

fading

chalking

chipping

cracking

peeling