

# Versa-Span™

## Produced in CA

Versa-Span™ system is a strong, durable, versatile, long length roof panel. It combines the strength of steel fluted pans and a lock-action rib design. Which together, with concealed fasteners, enables installation on low pitched roofs.

[ICC-ESR #5046 with CBC-CRC Supplement](#)

[UL Evaluation Report UL ER25913-01](#)

## Features & Benefits

### **Manufactured in Sacramento CA**

12", 14", 16" & 18" Coverage Options

24 and 22 Tru-Gauge™ and .032" and .040" Aluminum

1-3/4" Vertical Rib, factory notching available

2:12 minimum pitch recommended *(for lower pitches, please inquire)*

Standard panel lengths 1' to 60' *(for longer length panels, please inquire)*

On-site roll forming available for longer panels

Factory injected butyl sealant available

Clip relief is not standard, available upon request

Wide batten incorporates nicely over Versa-Span™ standing seam panel *(separate clip required)*

Weather-tightness warranty available (Contact NMP representative for details)



## Material Specifications

24 and 22 Tru-Gauge™ Kynar 500® Painted Steel

.032" Kynar 500® Painted Aluminum

24 Tru-Gauge™ G-90 Galvanized or AZ-50

24 and 22 Tru-Gauge™ bare Zincalume® Plus AZ-55 (*no finish warranty – 25 year perforation warranty*)

.040" Kynar 500® Painted Aluminum (*please inquire*)

24 Tru-Gauge™ Bonderized

22 gauge Rusteel Plus™ (A606)

Custom 20 & 18 Tru-Gauge™ and .050" and .063" Aluminum (*please inquire*)

16 and 20 ounce Real Copper

## Testing

UL Construction No. 254, 255, 261, 303, 342, 343, 414, 436, 445, 447, 448, 486, 508, 508A, 543, 544

UL 580 Class 90 Wind Uplift

UL 790 Class A (ASTM E108) – Fire rated

UL 2218 Class 4 – Impact (hail) rated

ASTM E1680 – Air infiltration (roof)

ASTM E1646 – Water infiltration (roof)

ASTM E1592 – Structural uniform static air pressure

ASTM E331 – Water infiltration (wall)

ASTM E283 – Air infiltration (wall)

ASTM E1514 – Standard for Structural Standing steel roof panels systems

ASTM A653/A924 – G90 Galvanized

ASTM A792 – Zincalume/Galvalume AZ-50/55

ASTM B209 – Aluminum substrate

ASTM E2886 – Ember Resistant ridge/endwall/peak flashings available

## Finishes

21 Standard Colors, 5 Metallic Colors and 4 Specialized Colors

**Vintage® has a color range that can vary from batch-to-batch and have directional variations**

For more information: [click here](#)

**Rusteel Plus™ has no metallic coating, is unpainted and has no warranty**

For more information: [click here](#)

Kynar 500® Paint System – the ultimate in exterior durability and color retention

“Cool” color pigments are specially designed to reflect infrared light, reducing heat gain to dwelling, and conform with ENERGY STAR® criteria

Superior quality, two-coat, 70% resin finish, applied at a 1 mil. thickness

40-year residential paint warranty

20 and 30 year commercial paint warranty: Contact NMP for warranty specifications